

ORDER CODE / OPTIONS

NTV 48-22 T - 1000 - XX		For some types several options possible. Available options depending on type or size.
RAIL TYPE		OPTIONS
NTA		AI = Aluminum
NTV		SB = Standard hole pattern (not required)
NTVZ		NZ = Design acc. drawing (e.g: customised hole pattern)
NTS		KK = Balls and cage stainless steel (standard for NX- and A-rails)
NTU		NC1 = Zinc-thick layer passivation (standard)
NTSU		NC4 = Zinc-nickel plated
		NC5 = Standard steel without coating
		NX2 = Stainless Steel Rail A2 Mat. 1.4301 (Load - 30%)
		NX4 = Stainless Steel Rail A4 Mat. 1.4571 (Load - 40%)
		EHG = Catch retracted rail
		EHO = Catch extended rail
		EOG = Catch double sided
		VG = Locking retracted rail
		VO = Locking extended rail
		VOG = Locking open and closed
		EDG = Damper, closed
		FDOG = Spring damper, open + closed
		VR = Forward and backward extension
		VRM = Forward and backward extension including carrier for inner rail
		AZ = Special extension length (not necessary for standard version) Example: NTV48-22T-1000-AZ1080 = Extension length 1080 mm
		LL = Smooth-running, for temperature up to 200°C or vertical installation
		LS = Increasing clearance, for temperature > 200°C
		G = Hardened
INSTALLATION SIZE		
ADDITION FOR SOME TYPES		
T = Sheetrail		
DC = Back-to-back assembly		
DS = 2 x I-beam (200 % extension)		
INSTALLATION LENGTH		

ORDER CODE LINEAR GUIDE SYSTEM

NTSF 50 - 2 - 120 - 2000		
RAIL TYPE		CARRIAGE LENGTH
INSTALLATION SIZE		
NUMBER OF CARRIAGES		RAIL LENGTH
Standard = 1 carriage (not necessary for standard version)		